

SAS to SAS RAID Subsystem

-- The RAID makes business continuity realized.

PRODUCT HIGHLIGHT

- Dual Flash ROM on each controller
- Support dual 12Gb/s bandwidth mini SAS ports
- Support up to 16 SAS / SATA II drives
- 3U rackmount, high density design
- No operating downtime and easy maintenance with:
 - Redundant, hot-swappable components
 - Modular architecture design
- User-friendly, web browser-based RAID management interface
- Event notification through e-mail or SNMP trap
- RoHS compliant system



SS-6652E

The RAID System setup an important milestone for MaxTronic approaching to critical high-end enterprise demands. Latest 3Gb SAS host interface with advanced high performance CPU supports higher data operation rate. Powerful hardware engine, high scalable expansion options and user-friendly management interface make it the best choice for fault tolerance, performance driven solutions.

FEATURES AND BENEFITS

Extreme Performance

Advanced 3Gb SAS host-transferring-speed with latest RISC CPU which delivers high performance for heavy duty business applications.

Better Firmware Protection

Dual Flash ROM on-board, embedded flash auto-backup function, supports higher system availability during firmware upgrading or single ROM failure.

Complete Data Protection

Various RAID Levels: JBOD, 0, 1, 3, 5, 6, 10, 30, 50, 60, or NRAID supported and complete RAID functions fulfill multiple data-redundancy requirements during system operation time.

Smart I/O Path Management

Just simple double-click installation, host-based PathGuard Software enables end-to-end I/O path failover & failback and dynamic I/O load balancing function to improve operation efficiency.



SAS



Technical Specifications



Host Channel	
Model No.	SS-6652E
Host Interface	Mini SAS
Data Transfer Rate	Up to 12Gb/s per port
Host Channel No.	2
JBOD Expansion	Yes(*1)
*1. Support up to 120 disks (include local chassis)	
Hardware	
Controller	Single
Controller CPU	AMCC PPC 440SP
Cache Memory	1024-4096 MB DDR II
Disk Interface	SAS (SATA II compatible)
Disk Channel No.	16
Hot Swap Disk Tray	16 x 3.5" swappable trays
Hot Swap Power Supply	460W x2 Redundant
AC Input Voltage	100 to 240V (+/-10%), 47 to 63 Hz
Battery Backup	Yes (optional)
Hot Swap Fan Module	2 x Turbo Fan
RAID Functions	
RAID Levels	JBOD, 0, 1, 3, 5, 6, 10, 30, 50, 60, NRAID
RAID Features	Support multiple RAID levels and stripe size Support local hot spare and global hot spare Online background initialization Online RAID level and stripe size migration Online disk group de-fragmentation for free space consolidation Online capacity expansion and shrink Online drive traveling and array roaming Online array recovery
RAID Management	
Front Panel LCD and Buttons	Easy access for configuration and status report
RS-232 Terminal	Command Line Interface (CLI) for configuration and status report
GUI	Web browser-based RAID management GUI for configuration and status monitoring
Event Notification	Built-in buzzer, e-mail, SNMP trap (*2), downloadable event records (up to 1024)
*2. Notification through e-mail or SNMP trap is supported by web browser-based GUI.	
Management AP	
PathGuard Software	Multiple paths to each device End-to-end I/O path failover and failback Dynamic I/O load balancing
RAIDGuard Central	Storage of complete event log records Convenient event log export feature Instant event log notification via MSN Multiple platforms support
Windows VDS	http://msdn2.microsoft.com/en-us/library/aa381442.aspx
Environment Specification	
Humidity	20% to 80% non-condensing
Operating Temperature	5°C to 40°C 41°F to 104°F
Non-operating Temperature	-25°C to 60°C -13°F to 140°F
Safety Regulatory	UL, CUL, CB
EMC Standard	FCC, CE, C-Tick, BSMI
Dimension and Weight	
Physical Dimension	485(W) x 565(D) x 132(H) mm
Physical Weight (without drives)	24 Kgs
Packed Dimension	610(W) x 790(D) x 450(H) mm
Packed Weight (without drives)	33 Kgs

* Specifications and product offerings may vary without notice.

* Various trademarks belong to their respective owners.

SS-6652E-0811060107

Headquarters

MaxTronic International Co., Ltd.
TEL : 886-2-2218 4875
FAX : 886-2-2218 4896
<http://www.maxtronic.com.tw>

America

Arena-MaxTronic Inc.
TEL : 1-626-334 1888
FAX : 1-626-334 6888
<http://www.maxtronic.com>

China

欧骉股份有限公司 北京代表处
TEL : 86-10-8280 0080
FAX : 86-10-8280 0784
<http://www.maxtronic.com.cn>